

AP-SSG25 Series Stump Grinder

RETURN TO INDEX

AVAILABLE FOR: SSV65 / SSV75 / SVL75-2 / SVL95-2s



Overall Mounting Width: 48"
 Overall Length (w/o Shielding): 60"
 Drive System: Hydraulic Motor w/Electric over Hydraulics
 Hydraulic Requirements: 17-32 gpm
 Angle & Lift Cylinders: 3" x 6" Stroke
 w/1 1/4" Rod Diameter
 Hydraulic Lines & Hoses: 3/4"
 Cutting Wheel: 1/2" Thick x 24" Diameter
 w/Carbide Teeth
 Number of Carbide Teeth: 32
 Cutting Wheel Speed: 640 rpm @ 18 gpm
 Cutting Arc: 55 Degrees
 Max Cutting Depth: 8"
 Greasable Hinge Points: Yes
 Main Frame: 6" x 6" x 1/4" Tube

MODEL NUMBER	DESCRIPTION	APPROX. MACHINE WEIGHT	SHIPPING WEIGHT	LIST PRICE
AP-SSG2524	25 SERIES STUMP GRINDER 24" Diameter Cutting Wheel	540#	650#	\$ 6,020
ADD OPTION NUMBER				
-20	Flat-Faced Hydraulic Quick Couplers (326-627A)	1#	1#	\$ 122
-31	Control Harness - Battery Connection with Switch	5#	5#	\$ 259
-32	14 Pin Wiring Harness (Kubota SVL & Others)	3#	3#	\$ 150
-35	2 Pin Wiring Harness (Kubota SVL w/0 14 Pin Connector)	3#	3#	\$ 305
-90	SSL/SVL Case Drain Coupler	2#	2#	\$ 48