

FDR16 Series Grooming Mowers

RETURN TO INDEX

15-30 HP



Made in USA
 Hitch: Cat. 1
 Lower Hitch: Floating
 Top Link: Floating
 Deck Thickness: 3/16"
 Gearbox: 540 rpm
 Cast Iron Housing, Beveled Gears
 Spring Loaded Idler
 Single B-Section Belt
 Gauge Wheels: 3 1/4" x 10" Solid Rubber
 Height Adjustment: 48: 3/4" - 3 1/4", 60/72: 3/4" - 5 1/4"
 1/2" Increment, Plated Spacers,
 1" Stress Proof® Caster Wheel Spindle
 Blade Spindle: 1 3/8", Cast Iron Greasable Hubs
 Blade Thickness: 1/4" Medium Lift - Hardened, Fusion® Edge
 Blade Overlap: 1 1/4"
 Blade Tip Speed: 16,203 - 18,130 fpm
 Driveline: Heavy Duty with Quick Coupler, Cat. 2
60" & 72" Fit Land Pride Quick-Hitch

Grooming Mower

MODEL NUMBER	DESCRIPTION	APPROX. MACHINE WEIGHT	SHIPPING WEIGHT	LIST PRICE
	48" FLAT DECK - REAR DISCHARGE			
FDR1648-13	4 Solid Rubber Tires	486#	545#	\$ 2,481
	60" FLAT DECK - REAR DISCHARGE			
FDR1660-13	4 Solid Rubber Tires	577#	642#	\$ 2,626
	72" FLAT DECK - REAR DISCHARGE			
FDR1672-13	4 Solid Rubber Tires	619#	700#	\$ 2,854

FDR16 ----- ADDITIONAL SAVINGS -----FDR16				
When 5 same color and width units are ordered at one time DEDUCT \$67 LIST ON EACH MOWER				
	ADD option No. -99 to Model Number and Deduct			\$ (67)

ADD OPTION NUMBER	COLOR OPTIONS
-82	Orange - 5 Pak and Single Units Available

ACCESSORIES available through the Parts Department:				
315-516S	Front Roller Assembly - 4" x 5.5"	5#	5#	\$ 71
890-700C	Mulching Blades - 48" - 3 ea. required			\$ 32
890-702C	Mulching Blades - 60" - 3 ea. required			\$ 32
890-698C	Mulching Blades - 72" - 3 ea. required			\$ 32