

# RCR18 Series - Utility Duty

RETURN TO INDEX

Cutters

20-65 HP



Side Skirt Thickness: 10 gauge  
 Gearbox Rating<sup>^</sup>: 65 HP  
 Gearbox: 540 RPM, Beveled Gears, Cast Iron Housing  
 Driveline: Cat. 3; Center Shear Bolt  
 or 2-Plate Slip-Clutch  
 Front Rubber Optional  
 Rear Rubber Optional  
 Rear Metal Band Standard  
 Blade Holder Bar with Stump Jumper  
 Blades: 2 ea. (1/2" x 3" Heat Treated)  
 Free Swinging Alloy Steel Suction Blades  
 Blade Bolt: Keyed with Hardened Flat Washer &  
 Lock Nut  
 Blade Speed: 16,363 fpm on 60"; 14,853 fpm on 72"  
 Tailwheel: 15" Laminated Tire with Cast Iron Hub  
 or 4" x 16" Molded Rubber - 360 Degree Swivel  
 Cutting Height: 60": 1 1/2" - 13"; 72: 1 1/2" - 11 1/2"  
 Skids: Weld-on  
 Fits Land Pride Quick-Hitch

Made in USA  
 Hitch: Cat. 1; Floating Clevis Type Top Link  
 and Clevis Type Lower Links  
 All Welded Deck  
 Deck Height: 60" - 7 1/2"; 72" - 9"  
 Cutting Capacity: 2"  
 Deck Thickness: 60" - 11 gauge; 72" - 10 gauge

\*Bolt on Skid Shoes Available through Parts Dept.

| MODEL NUMBER                         | DESCRIPTION                                 | APPROX. MACHINE WEIGHT | SHIPPING WEIGHT | LIST PRICE |
|--------------------------------------|---|------------------------|-----------------|------------|
| <b>18 SERIES - 60" ROTARY CUTTER</b> |   |                        |                 |            |
| RCR1860                              | -11 -31 Laminated Tailwheel, Shear Bolt     | 571#                   | 669#            | \$ 1,813   |
|                                      | -11 -32 Laminated Tailwheel, Slip-Clutch    | 584#                   | 682#            | \$ 1,973   |
|                                      | -12 -31 Molded Rubber Tailwheel, Shear Bolt | 558#                   | 656#            | \$ 1,848   |
| <b>Choose a Front Guard</b>          |   |                        |                 |            |
| ADD -01                              | Front Rubber Guard (312-844A)               | 15#                    | 15#             | \$ 50      |
| ADD -02                              | Front Chain Guard (312-845A)                | 50#                    | 50#             | \$ 144     |
| <b>Choose a Rear Guard</b>           |   |                        |                 |            |
| ADD -42                              | Rear Rubber Guard (312-652A)                | 23#                    | 23#             | \$ 52      |
| ADD -41                              | Rear Chain Guard (312-834A)                 | 46#                    | 46#             | \$ 157     |
| <b>18 SERIES - 72" ROTARY CUTTER</b> |   |                        |                 |            |
| RCR1872                              | -11 -31 Laminated Tailwheel, Shear Bolt     | 704#                   | 822#            | \$ 2,318   |
|                                      | -11 -32 Laminated Tailwheel, Slip-Clutch    | 715#                   | 833#            | \$ 2,476   |
|                                      | -12 -31 Molded Rubber Tailwheel, Shear Bolt | 691#                   | 809#            | \$ 2,353   |
| <b>Choose a Front Guard</b>          |   |                        |                 |            |
| ADD -01                              | Front Rubber Guard (312-846A)               | 22#                    | 22#             | \$ 56      |
| ADD -02                              | Front Chain Guard (312-847A)                | 60#                    | 60#             | \$ 171     |
| <b>Choose a Rear Guard</b>           |   |                        |                 |            |
| ADD -42                              | Rear Rubber Guard (312-651A)                | 23#                    | 23#             | \$ 57      |
| ADD -41                              | Rear Chain Guard (312-842A)                 | 46#                    | 46#             | \$ 188     |

**ADDITIONAL SAVINGS**  
**RCR 5-PAK STOCKING PROGRAM**

When 5 same color, width and optioned units are ordered at one time - DEDUCT \$47 List on each cutter  
 Add option No. -99 to Model Number & Deduct \$ (47)

**ADD OPTION NO.**      **COLOR OPTIONS**  
 -82      Orange - 5 Pak and Single units available

**WARNING!** Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.

<sup>^</sup>Gearbox HP rating is based on in field use and performance

# RCR18 Series - Utility Duty

RETURN TO INDEX

45-90 HP



Made in USA  
 Hitch: Cat. 1 and 2; Floating Clevis Type Top Link and Clevis Type Lower Links  
 All Welded Deck  
 Deck Height: 9<sup>1</sup>/<sub>8</sub>"  
 Deck Thickness: 10 gauge  
 Cutting Capacity: 2"  
 Gearbox Rating<sup>^</sup>: 130 HP  
 Gearbox: 540 RPM, Beveled Gears, Cast Iron Housing  
 Driveline: Cat. 4; 2-Plate Slip-Clutch  
 Front Rubber or Chain Guard  
 Rear Chain Guard Optional  
 Rear Metal Band Standard  
 Blade Holder Bar with Stump Jumper  
 Blades: 2 ea. (1<sup>1</sup>/<sub>2</sub>" x 4" Heat Treated)  
 Free Swinging Alloy Steel Suction Blades  
 Blade Bolt: Keyed with Hardened Flat Washer & Lock Nut  
 Blade Speed: 17,100 fpm  
 Tailwheel: 15" Laminated Tire with Cast Iron Hub  
 Cutting Height: 2"-11"  
 Skids: Weld-on  
 Fits Land Pride Quick-Hitch

| MODEL NUMBER          | DESCRIPTION                          | APPROX. MACHINE WEIGHT | SHIPPING WEIGHT | LIST PRICE |
|-----------------------|--------------------------------------|------------------------|-----------------|------------|
| RCR1884               | <b>18 SERIES - 84" ROTARY CUTTER</b> | 827#                   | 907#            | \$ 3,275   |
| <b>ADD OPTION NO.</b> | <b>Choose Front Guarding</b>         |                        |                 |            |
| -01                   | Front Rubber Guard (312-866A)        | 24#                    | 24#             | \$ 87      |
| -02                   | Front Chain Guard (312-869A)         | 41#                    | 41#             | \$ 181     |
|                       | <b>Choose One Tailwheel Package</b>  |                        |                 |            |
| -16                   | Single Laminated Tailwheel           | 105#                   | 105#            | \$ 356     |
| -17                   | Dual Laminated Tailwheel             | 234#                   | 234#            | \$ 756     |
|                       | <b>Choose Rear Guarding</b>          |                        |                 |            |
| -41                   | Rear Chain Guard (312-872A)          | 80#                    | 80#             | \$ 199     |
| <b>ADD OPTION NO.</b> | <b>COLOR OPTIONS</b>                 |                        |                 |            |
| -81                   | Green                                |                        |                 |            |
| -82                   | Orange                               |                        |                 |            |
| -83                   | Red                                  |                        |                 |            |

<sup>^</sup>Gearbox HP rating is based on in field use and performance

**WARNING!** Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.