

FDR25 Series Grooming Mowers

RETURN TO INDEX

15-50 HP



Made in USA
 Hitch: Cat. 1
 Lower Hitch: Floating & Adjustable
 Clevis Type with Plated Pins
 Top Link: Floating & Adjustable
 Welded Tubular Chassis
 Deck Thickness: 3/16"
 Gearbox: 540 rpm
 Cast Iron Housing
 Beveled Gears
 Single B-Section Belt
 Spring Loaded Idler
 Gauge Wheels: 3 3/4" x 10" Solid Rubber Tires
 w/Bearings
 FDR2584: 4" x 11" Semi-Solid Tires
 Height Adjustment: 3/4" - 5 1/4" in 1/2" Increments
 Plated Spacers, 1" Stress Proof® Caster Wheel Spindle
 Blade Spindle: 1 3/8", Cast Iron Greaseable Hubs
 Blade Thickness: 1/4" (5/16" on 84")
 Medium Lift - Hardened
 Blade Overlap: 1 1/4"
 Blade Tip Speed (fpm);
 72: 18,130, 84: 17,210
 Heavy Duty Driveline with Quick Coupler
 Fits Land Pride Quick-Hitch

MODEL NUMBER	DESCRIPTION	APPROX. MACHINE WEIGHT	SHIPPING WEIGHT	LIST PRICE
	25 SERIES - REAR DISCHARGE - 72"			
FDR2572-13	4 Solid Rubber Tires	718#	781#	\$ 3,745
FDR2572-14	4 Solid Rubber Tires and Front Roller	726#	789#	\$ 3,867
	25 SERIES - REAR DISCHARGE - 84"			
FDR2584-13	4 Semi-Solid Tires & Bearings	812#	878#	\$ 4,331
FDR2584-14	4 Semi-Solid Tires with Bearings and Front Roller	820#	886#	\$ 4,451

ADD OPTION NUMBER	COLOR OPTION
-82	Orange

ACCESSORIES Available through the Parts Department				
MODEL NUMBER	DESCRIPTION	APPROX. MACHINE WEIGHT	SHIPPING WEIGHT	LIST PRICE
310-254S	Front Roller - 4" x 10" for 72 & 84	8#	8#	\$ 124
890-698C	Mulching Blades - 72" - 3 ea. required			\$ 32
890-706C	Mulching Blades - 84" - 3 ea. required			\$ 32