

RCF20 Series - Utility Duty - Smooth Top

RETURN TO INDEX

Cutters

20-65 HP



Made in USA
 Hitch: Cat. 1; Floating Top Link
 Quick-Hitch Adaptable
 All Welded Deck
 Deck Height: 60" - 9¹¹/₁₆"; 72" - 11"
 Cutting Capacity: 2"
 Cutting Height: 1¹/₂" - 12"

Deck Thickness: 10 gauge
 Side Skirt: 10 Gauge
 Gearbox Rating[^]: 65 HP
 Gearbox: 540 RPM, Beveled Gears
 Cast Iron Housing
 Driveline: Cat. 3; Shear Bolt
 or 2-Plate Slip-Clutch
 Optional Front Guard: Rubber or Chain
 Standard Rear Metal Banding
 Optional Rear Guard: Rubber or Chain
 Blade Holder Bar with Stump Jumper
 Blades: 2 ea. (1/2" x 3" Heat Treated)
 Free Swinging High-Lift, Low Friction Blades
 Blade Bolt: Keyed with Hardened Flat Washer & Lock Nut
 Blade Speed: 16,363 fpm on 60"; 14,955 fpm on 72"
 Tailwheel: Single or Dual, 4" x 15" Laminated Tire
 or 4" x 16" Molded Rubber - 360 Degree Swivel
 Skids: Weld-on
 Fits Land Pride Quick-Hitch

*Bolt on Skid Shoes Available through Parts Dept.

| MODEL NUMBER | DESCRIPTION | APPROX. MACHINE WEIGHT | SHIPPING WEIGHT | LIST PRICE |
|--------------|--------------------------------------|------------------------|-----------------|------------|
| RCF2060 | 20 SERIES - 60" ROTARY CUTTER | | | |
| -11 -31 | Laminated Tailwheel, Shear Bolt | 590# | 688# | \$ 1,980 |
| -11 -32 | Laminated Tailwheel, Slip-Clutch | 603# | 701# | \$ 2,140 |
| -12 -31 | Molded Rubber Tailwheel, Shear Bolt | 577# | 675# | \$ 2,015 |
| | Choose a Front Guard | | | |
| ADD -01 | Front Rubber Guard (312-844A) | 17# | 17# | \$ 50 |
| ADD -02 | Front Chain Guard (312-845A) | 24# | 24# | \$ 144 |
| | Choose a Rear Guard | | | |
| ADD -42 | Rear Rubber Guard (312-652A) | 20# | 20# | \$ 52 |
| ADD -41 | Rear Chain Guard (312-834A) | 29# | 29# | \$ 157 |
| RCF2072 | 20 SERIES - 72" ROTARY CUTTER | | | |
| -11 -31 | Laminated Tailwheel, Shear Bolt | 712# | 830# | \$ 2,485 |
| -11 -32 | Laminated Tailwheel, Slip-Clutch | 723# | 841# | \$ 2,643 |
| -12 -31 | Molded Rubber Tailwheel, Shear Bolt | 699# | 817# | \$ 2,597 |
| | Choose a Front Guard | | | |
| ADD -01 | Front Rubber Guard (312-846A) | 22# | 22# | \$ 56 |
| ADD -02 | Front Chain Guard (312-847A) | 39# | 39# | \$ 171 |
| | Choose a Rear Guard | | | |
| ADD -42 | Rear Rubber Guard (312-651A) | 23# | 23# | \$ 57 |
| ADD -41 | Rear Chain Guard (312-842A) | 40# | 40# | \$ 188 |

ADDITIONAL SAVINGS
RCR 5-PAK STOCKING PROGRAM

When 5 same color, width and optioned units are ordered at one time - DEDUCT \$47 List on each cutter
 Add option No. -99 to Model Number & Deduct \$ (47)

| ADD OPTION NO. | COLOR OPTIONS | |
|----------------|---|-------|
| -82 | Orange - 5 Pak and Single units available | |
| | Available Through Parts Dept. Only | |
| 326-120A | Bolt-on Skid Shoes - 60" & 72" | \$ 40 |

[^]Gearbox HP rating is based on in field use and performance

WARNING! Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.

RCF20 Series - Utility Duty - Smooth Top

RETURN TO INDEX

45-90 HP



Made in USA
 Hitch: Cat. 1 and 2; Floating Top Link
 Clevis Type Lower Links, Quick-Hitch Adaptable
 Cutting Height: 1 1/2"-12"
 All Welded Deck
 Deck Height: 11 15/16"
 Deck Thickness: 10 gauge
 Side Skirt: 10 Gauge
 Cutting Capacity: 2"
 Gearbox Rating^: 130 HP
 Gearbox: 540 RPM, Beveled Gears, Cast Iron Housing
 Driveline: Cat. 4; 2-Plate Slip-Clutch
 Optional Front Guard: Rubber or Chain
 Optional Rear Chain Guard
 Standard Rear Metal Band
 Blade Holder Bar with Stump Jumper
 Blades: 2 ea. (1 1/2" x 4" Heat Treated)
 Free Swinging Alloy Steel Suction Blades
 Blade Bolt: Keyed with Hardened Flat Washer & Lock Nut
 Blade Speed: 17,113 fpm
 Tailwheel: 4" x 15" Laminated Tire w/Cast Iron Hub
 - 360 Degree Swivel
 Skids: Weld-on
 Fits Land Pride Quick-Hitch

*Bolt on Skid Shoes Available through Parts Dept.

| MODEL NUMBER | DESCRIPTION | APPROX. MACHINE WEIGHT | SHIPPING WEIGHT | LIST PRICE |
|-----------------------|---|------------------------|-----------------|------------|
| RCF2084 | 20 SERIES - 84" ROTARY CUTTER | 915# | 1000# | \$ 3,441 |
| ADD OPTION NO. | Choose Front Guarding | | | |
| -01 | Front Rubber Guard | 24# | 24# | \$ 87 |
| -02 | Front Chain Guard | 41# | 41# | \$ 181 |
| | Choose One Tailwheel Package | | | |
| -16 | Single Laminated Tailwheel | 108# | 108# | \$ 356 |
| -17 | Dual Laminated Tailwheel | 240# | 240# | \$ 756 |
| | Choose Rear Guarding | | | |
| -41 | Rear Chain Guard | 62# | 62# | \$ 199 |
| ADD OPTION NO. | COLOR OPTIONS | | | |
| -81 | Green | | | |
| -82 | Orange | | | |
| -83 | Red | | | |
| | Available Through Parts Dept. Only | | | |
| 326-120A | Bolt-on Skid Shoes - 84" | | | \$ 40 |

^Gearbox HP rating is based on in field use and performance

WARNING!

Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.