60: 50-190 HP • 72: 60-190 HP







Hitch: Cat. 1* or 2 (QH Adaptable)

All Welded Deck Deck Height: 133/8" Deck Thickness: 3/16" Side Panels: 1/4"

Gearbox Rating^: 210 HP Gearbox: 540 RPM, 13/4" - 20 Spline

Gearbox Output Shaft: 23/8"

Driveline: Cat. 5 with 4 Plate Slip-Clutch

Stump Jumper: 3/16"

Blades: Free Swinging High Lift

60" - ½" x 4" x 23" 72" - ½" x 4" x 29"

Blade Bolt: Keyed with Hardened Flat Washer & Lock Nut

Blade Tip Speed: 60" - 13,572 fpm 72" - 14,861 fpm

Tailwheel(s): 15" Laminated, with Cast Iron Hub, Tapered Roller Bearings, 21" on Pull-Type

Cutting Height: 2" - 12" Cutting Capacity: 4" Skids: Replaceable

Front and Rear Chain Guards Available

MODEL NUMBER	DESCRIPTION		APPROX. MACHINE WEIGHT	SHIPPING WEIGHT	LIST PRICE	
RCF3660	36 SERIES - 60" ROTARY O	CUTTER	1147#	1,227#	\$	4,335
	Choose Front Guarding			0.00 (0.0000000000000000000000000000000	10.400	
-01	Front Chain Guard	(326-177A)	46#	46#	\$	207
-02	Front Rubber Guard	(326-254A)	19#	19#	\$	151
-03	Front Double Chain Guard	(326-255A)	63#	63#	\$	273
	Choose Rear Guarding					
-41	Rear Chain Guard	(326-310A)	40#	40#	\$	312
-43	Rear Double Chain Guard	(326-318A)	57#	57#	\$	414
-45	Rear Band Guard	(326-269A)	30#	30#	\$	N/C
	You Must Choose One					
-90	Standard Blade Carrier - 60		112#			N/C
-91	Shredder Kit		142#		\$	639
RCF3672	36 SERIES - 72" ROTARY O	CUTTER	1,238#	1,318#	\$	5,017
	Choose Front Guarding		F TO ★ PCASA AND	Cont Description	0.00	1-0 4 140000-0
-01	Front Chain Guard	(326-200A)	55#	55#	\$	241
-02	Front Rubber Guard	(326-256A)	23#	23#	\$	166
-03	Front Double Chain Guard	(326-257A)	75#	75#	\$	325
	Choose Rear Guarding					
-41	Rear Chain Guard	(326-317A)	44#	44#	\$	347
-43	Rear Double Chain Guard	(326-319A)	64#	64#	\$	441
-45	Rear Band Guard	(326-270A)	35#	35#	\$	N/C
	You Must Choose One					
-90	Standard Blade Carrier - 72		166#			N/C
-91	Shredder Kit		170#		\$	639
ADD OPTION NO.	COLOR OPTION					

-82 Orange

Available Through Parts Dept. Only

326-607A *Requires Top 3 Pt Cat 2/Cat 1 Conversion Kit

^Gearbox HP rating is based on in field use and performance

WARNING Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.

84 Lift: 70-190 HP • Pull: 50-190 HP







Hitch: Cat. 2 or Cat. 3 (QH Adaptable)

All Welded Deck Deck Height: 13³/s" Deck Thickness: ³/16" Side Panels: ¹/4"

Gearbox Rating^: 225 HP

Gearbox: 540 RPM, 13/4" - 20 Spline

Gearbox Output Shaft: 23/8"

Driveline: Cat. 5 with 4 Plate Slip-Clutch

Stump Jumper: 3/16"

Blades: Free Swinging High Lift

1/2" x 4" x 29"

Blade Bolt: Keyed with Hardened Flat Washer & Lock Nut Blade Tip Speed: 14,369 fpm

Blade Tip Speed: 14,369 fpm
Tailwheel(s): 15" Laminated, with Cast Iron Hub,
Tapered Roller Bearings, 21" on Pull-Type

Cutting Height: 2" - 12" Cutting Capacity: 4" Skids: Replaceable

Front and Rear Chain Guards Available

MODEL NUMBER	DESCRIPTION		APPROX. MACHINE WEIGHT	SHIPPING WEIGHT 1,449#	LIST PRICE	
RCF3684	36 SERIES - 84" ROTARY CUT	1,369#	\$		4,716	
	Choose Front Guarding					
-01	Front Chain Guards (3	326-661A)	64#	64#	\$	274
-02	Front Rubber Guard (3	326-258A)	26#	26#	\$	180
-03	Front Double Chain Guards (3	326-662A)	94#	94#	\$	666
	You Must Choose One					
*-12	Pull-Type with Dual 21" Lamina	ated Tires	565#	565#	\$	2,448
-14	3 Point with Dual 15" Laminate	ed Tires	501#	501#	\$	2,103
	You Must Choose One for 3-P	oint				
-21	Ratchet Height Adjustment		15#	15#	\$	215
-23	Hydraulic Height Adjustment		40#	40#	\$	397
	You Must Choose One for Pull-Type					
-21	Ratchet Height Adjustment		15#	15#	\$	215
-22	Hydraulic Type Adjustment		40#	40#	\$	447
	You Must Choose Rear Guarding					
-41	Rear Chain Guard (3	326-184A)	66#	66#	\$	443
-43	Rear Double Chain Guards (3	326-264A)	83#	83#	\$	648
-45	Rear Band Guard (3	326-271A)	40#	40#	\$	N/C
	You Must Choose One					
-90	Standard Blade Carrier - 84"		220#			N/C
-91	Shredder Kit		200#		\$	639
ADD OPTION NO.	COLOR OPTION					
-81	Green					

-81 Green -82 Orange -83 Red

*Gearbox HP rating is based on in field use and performance

Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.