

RCR15 Series - Utility Duty

RETURN TO INDEX

20-60 HP



Made in USA
 Hitch: Cat. 1 & Cat. 1 Limited; 3-Point with Floating
 Clevis Type Top Link
 One Piece Reinforced Deck
 Deck Height: 7 1/4"
 Deck Thickness: 12 Gauge
 Gearbox Rating[^]: 65 HP
 Gearbox: 540 RPM, Beveled Gears, Cast Iron Housing
 Driveline: Cat. 3; 1/2" Center Shear Bolt
 or 2-Plate Slip-Clutch
 Optional Front and Rear Rubber Guard
 Stump Jumper
 Blades: 2 ea. (1/2" x 3" Heat Treated)
 Free Swinging Alloy Steel Suction Blades
 Blade Bolt: Keyed with Hardened Flat Washer
 & Lock Nut
 Blade Speed: 11,459 fpm on 42"; 13,090 fpm on 48"
 Tailwheel: 4" x 16" Molded Rubber - 360 Degree Swivel
 Cutting Height: 1 3/4" - 11 1/2"
 Cutting Capacity: 2"
 Skids: Weld-on
 Fits Land Pride Quick-Hitch

MODEL NUMBER	DESCRIPTION	APPROX. MACHINE WEIGHT	SHIPPING WEIGHT	LIST PRICE
RCR1548	15 SERIES - 48" ROTARY CUTTER			
	-01123142 Molded Rubber Tailwheel, Shear Bolt Driveline Front and Rear Rubber Guard	424#	514#	\$ 1,652
	For Laminated Tailwheel DELETE -12 from Model No. and ADD -11		41#	\$ (35)
	For Slip-Clutch Driveline DELETE -31 from Model No. and ADD -32		36#	\$ 156
	TO DELETE GUARDING			
	Front Rubber Guard DELETE -01 from Model No. (312-672A)	10#	10#	\$ (49)
	Rear Rubber Guard DELETE -42 from Model No. (312-673A)	10#	10#	\$ (31)

ADDITIONAL SAVINGS
RCR 5-PAK STOCKING PROGRAM
 When 5 same color, width and optioned units are ordered at one time - DEDUCT \$45 List on each cutter

Add option No. -99 to Model Number & Deduct \$ (45)

ADD OPTION NO.	COLOR OPTIONS
-82	Orange - 5 Pak and Single units available

[^]Gearbox HP rating is based on in field use and performance

WARNING!
 Rotary Cutters used in non-agricultural areas must be equipped with front & rear guards. The possibility of thrown objects can be hazardous to persons or property.