

DT55 Series Ditchers

RETURN TO INDEX

60-150 HP



Cat. 2 & 3, QH Adaptable
 Impeller: 20", 6 Blades with Replaceable
 Hardened Cutting Edges
 Double 80 Chain with Positive Tensioner Bolt
 Input/Output Shafts: 2-1/4", with Ball Type Bearings
 Driveline: Cat. 5 with Shear Bolt

OPTIONAL EQUIPMENT

Material Control Chute: Manual or Hydraulic
 Depth Control Wheel: 16.5 x 6.50-8 Pneumatic Tire
 with 10" Adjustment
 Deep Ripper Shank: 3 Adjustments to 5" Below
 Cutting Level, Spring Tine Tip
 Depth Controlling Skid Shoe: Replaceable, 3/8" Thick

Dirtworking

<u>MODEL NUMBER</u>	<u>BASE UNIT</u>	<u>APPROX. MACHINE WEIGHT</u>	<u>SHIPPING WEIGHT</u>	<u>LIST PRICE</u>
DT55	55 SERIES POWERED DITCHER - 540 RPM 1 ³ / ₈ " 6 Spline	900#	950#	\$ 5,126
DTM55	55 SERIES POWERED DITCHER - 1000 RPM (You must choose a driveline below)	850#	900#	\$ 4,432
	Driveline Option for DTM only			
-31	Cat. 5 Shear Bolt - 1 ³ / ₈ " - 21 Spline	50#	50#	\$ 695
-32	Cat. 5 Shear Bolt - 1 ³ / ₄ " - 21 Spline	50#	50#	\$ 695
ADD OPTION NUMBER	OPTIONAL EQUIPMENT			
-12	Depth Controlling Gauge Wheel (324-050A)	40#	40#	\$ 265
-21	Ripper Shank with Toolbar (324-046A)	157#	157#	\$ 556
-41	Material Chute - Ratchet Adjustment (324-070A)	114#	114#	\$ 357
-42	Material Chute - Hydraulic Adjustment (324-071A)	115#	115#	\$ 475
-51	Skid Shoe (324-056A)	15#	15#	\$ 114
	COLOR			
-82	Orange			